

модель	поток вопрос мЗ/ч	Поднимат ь ЧАС м	Скорость н об/мин	Мощность двигателя ш
40PV—SP	7.2	5.5	1000	1.1
	12.6	5		
	18	4.3		
40PV—SP	9	8	1200	1.5
	15.12	7.4		
	21.6	6.4		
40PV—SP	10.08	10.9	1400	2.2
	18	10		3
	24.81	8.7		4
40PV—SP	10.44	11.5	1420	2.2
	18	10.5		3
	25.2	9		4
40PV—SP	10.8	12.7	1500	3
	18.72	11.3		4
	26.64	10		5
40PV—SP	11.52	14.4	1600	3
	19.8	13		4
	28.08	11.2		5
40PV—SP	12.24	16.4	1700	4
	21.24	15		5.5
	30.24	12.9		7
40PV—SP	13.32	18.2	1800	4
	22.68	16.8		5.5
	32.04	14.5		7
40PV—SP	14.04	20.5	1900	5.5
	24.12	18.7		7.5
	34.2	16		9
40PV—SP	14.76	22.5	2000	5.5
	25.2	20.6		7.5
	36	17.6		9
40PV—SP	15.48	24.9	2100	7.5
	26.64	22.5		
	37.8	19.5		
40PV —SP	16.2	27.4	2200	7.5
	28.8	24.6		11
	39.6	21.4		15
	8.81	6.74		

50QV—SP	14.69	5.99	710	2.2
	21.3	5.21		
50QV—SP	9.93	8.56	800	2.2
	16.55	7.67		
	24	6.61		
50QV—SP	11.17	10.83	900	3
	18.62	9.63		
	27	8.37		
50QV—SP	11.92	12.33	900	2
	19.86	10.96		3
	28.8	9.52		4
50QV —SP	13.66	16.18	1100	5.5
	22.76	14.39		
	33	12.5		
50QV—SP	14.9	19.26	1200	7.5
	24.83	17.12		
	36	14.88		
50QV—SP	16.44	22.6	1300	5
	26.9	20.1		7.5
	39	17.46		11
50QV—SP	18	28.12	1450	8
	30	25		11
	43.5	21.73		14
50QV—SP	18.62	30.09	1500	7
	31.03	26.75		11
	45	23.25		15
50QV—SP	19.86	34.24	1600	12
	33.1	30.44		15
	48	26.45		18.5
50QV—SP	21.1	38.65	1700	15
	35.17	34.36		18.5
	51	29.86		22
50QV—SP	22.34	43.34	1800	22
	37.24	38.53		
	54	33.48		
65QV—SP	19.08	6.7	700	3
	34.2	6		
	48.6	5		
65QV—SP	20.16	7	710	2.2
	34.92	6.4		3
	49.3	5.4		4
	21.6	8.9		2.2

65QV SP	39.6	7.9	800	3
	55.08	6.8		4
65QV —SP	24.48	11.1	900	3
	43.2	9.9		4
	61.2	8.5		5.5
65QV —SP	26.28	12.8	960	4
	46.08	11.4		5.5
	65.88	9.8		7.5
65QV—SP	30.21	16.8	1100	5.5
	51	14.8		7.5
	75.6	12.8		11
65QV—SP	32.4	19.6	1200	7.5
	57.6	17.7		11
	81.72	15.2		15
65QV SP	35.28	23.1	1300	11
	61.2	20.8		15
	82.2	17.8		18.5
65QV —SP	37.8	26.7	1400	11
	66.6	24		15
	95.4	20.5		18.5
65QV —SP	39.6	29.3	1470	15
	70.2	26.1		18.5
	100.08	22.7		22
65QV —SP	40.3	30.8	1500	15
	72	27.4		18.5
	102.6	23.5		22
65QV(II)-SP	14.5	7.7	710	2
	24.1	7		2.2
	35	6.3		3
65QV(II)-SP	16.3	9.8	800	2
	27.2	8.9		3
	39.5	8		4
65QV(II)-SP	18.4	12.4	900	3
	30.6	11.2		4
	44.4	10.1		5.5
65QV(II)-SP	19.6	14.1	960	4
	32.7	12.8		5.5
	47.3	11.5		7.5
65QV(II)-SP	22.4	18.5	1100	7.5
	37.4	16.8		11
	54.3	15.1		15
	24.5	22		11

65QV(II)-SP	40.8	20	1200	15
	59.2	18		18.5
65QV(II)-SP	26.5	25.8	1300	15
	44.2	23.5		15
	64.1	21.1		15
65QV(II)-SP	30	33	1470	18.5
	50	30		22
	72.5	27		25
65QV(II)-SP	30.6	34.4	1500	18.5
	51	31.2		22
	74	28.1		25
80RV-SP	38.21	8.46	650	5.5
	63.68	7.91		
	92.34	7.02		
80RV-SP	42.91	10.67	730	7.5
	71.52	9.97		11
	103.7	8.86		12
80RV-SP	47.03	12.81	800	9
	78.38	11.98		11
	113.65	10.64		15
80RV-SP	52.91	16.22	900	11
	88.18	15.16		15
	127.85	13.46		18.5
80RV-SP	57.61	19.23	980	18.5
	96.01	17.98		22
	139.22	15.98		25
80RV-SP	64.68	24.22	1100	22
	107.77	22.65		30
	156.27	20.13		35
80RV-SP	70.54	28.83	1200	30
	117.57	26.95		37
	170.47	23.94		45
80RV-SP	76.42	34.38	1300	37
	127.36	31.63		45
	184.68	27.49		52
80RV-SP	82.3	39.8	1400	45
	137.1	36.6		
	198.8	31.8		
80RV-SP	87	44.09	1480	45
	145	41		
	203	35.51		
	41.5	6.2		3

100RV-SP	75.6	5.9	500	4
	111.6	5.1		5.5
100RV-SP	50.4	9	600	5.5
	90	8.5		7.5
	129.6	7.6		11
100RV-SP	57.6	12.2	700	7.5
	104.4	11.5		11
	151.2	10.2		15
100RV-SP	61.2	13.4	730	7.5
	111.6	12.7		11
	162	11.2		15
100RV-SP	64.8	16	800	11
	122.4	15		15
	176.4	13.2		18.5
100RV-SP	68.4	18	850	15
	129.6	17		18.5
	187.2	15		22
100RV-SP	75.6	20.3	900	22
	136.8	18.9		30
	198	16.9		37
100RV-SP	82.8	24	980	30
	147.6	22.5		37
	214.2	20		45
100RV-SP	84.5	25	1000	22
	151.2	23.4		30
	219.6	20.8		37
100RV-SP	86.4	27.7	1050	30
	158.4	25.7		37
	230.4	22.8		45
100RV-SP	91.8	30.3	1100	37
	165.6	28.2		45
	239.4	25.2		52
100RV-SP	95.4	33	1150	30
	172.8	31		37
	252	27.5		45
100RV-SP	100.8	36	1200	45
	180	33.8		
	259.2	30		
150SV-SP	115.2	9	500	9
	201.6	8		11
	288	6.7		15
	129.6	10.8		15

150SV-SP	223.2	9.7	550	18.5
	316.8	8		22
150SV-SP	140.4	12.9	600	22
	244.8	11.4		30
	345.6	9.6		45
150SV-SP	154.2	15.2	650	30
	262.8	13.5		37
	374.4	11.4		45
150SV-SP	165.6	17.5	700	30
	280.8	15.7		37
	396	13.2		45
150SV-SP	169.2	19	730	30
	295.2	17		37
	417.6	14.5	740	45
150SV-SP	187.2	22.9	800	37
	324	20.4		45
	457.2	17.1		55
150SV-SP	201.6	25.5	850	45
	345.6	22.9		55
	486	19.3		75
150SV-SP	212.4	28.9	900	55
	367	25.7		75
	518.4	21.7		90
150SV-SP	223.2	31.4	940	55
	381.6	28		75
	540	23.5		90
150SV-SP	230.4	33.5	980	90
	396	30.2		
	561.6	25.4		
150SV-SP	234	35.7	1000	90
	403.2	31.9		
	576	26.8		
200SV-SP	183.6	8.2	400	11
	327.6	7.1		15
	471.6	5.9		18.5
200SV-SP	198	10.4	450	18.5
	356.4	9.2		22
	511.2	7.8		30
200SV-SP	215.2	12.4	490	22
	377.5	10.9		30
	536.3	9.4		37
	219.6	12.9		22

200SV-SP	385.2	11.4	500	30
	547.2	9.8		37
200SV-SP	244.8	15.5	550	30
	410.4	13.9		37
	586.8	11.9		45
200SV-SP	262	17.9	590	37
	435.4	16.1		45
	616	14		55
200SV-SP	266.4	18.5	600	37
	442.8	16.7		45
	626.4	14.5		55
200SV-SP	291.6	21.8	650	45
	475.2	19.7		55
	666	17.1		75
200SV-SP	316.8	25.2	700	55
	504	22.9		75
	705.6	20		90
200SV-SP	330.3	28.2	740	90
	529.2	25.6		110
	735.3	22.6		
200SV-SP	334.8	29	750	90
	536.4	26.3		110
	745.2	23.2		
200SV-SP	360	33	800	90
	568.8	30		110
	784.8	26.7		132
200SV-SP	381.6	37.2	850	110
	597.6	34		132
	824.4	30.2		160
250TV-SP	380	34.2	750	110
	500	33.5		120
	700	32.0		132
250TV-SP	355	29.8	700	110
	467	29.2		110
	653	27.9		110
250TV-SP	329	25.7	650	75
	433	25.2		75
	607	24.0		75
250TV-SP	304	21.9	600	55
	400	21.4		60
	560	20.5		75
	279	18.4		45

250TV-SP	367	18.0	550	50
	513	17.2		55
250TV-SP	253	15.2	500	37
	333	14.9		37
	467	14.2		37
250TV-SP	228	12.3	450	30
	300	12.1		30
	420	11.5		30
250TV-SP	203	9.7	400	18.5
	267	9.5		20
	373	9.1		22
300TV-SP	450	27.8	700	110
	820	25.8		120
	1100	24.0		132
300TV-SP	418	24.0	650	90
	761	22.2		100
	1021	20.7		110
300TV-SP	386	20.4	600	75
	703	18.9		82
	943	17.6		90
300TV-SP	354	17.2	550	55
	644	15.9		65
	864	14.8		75
300TV-SP	321	14.2	500	45
	586	13.2		50
	786	12.2		55
300TV-SP	289	11.5	450	30
	527	10.7		33
	707	9.9		37
300TV-SP	257	9.0	400	22
	469	8.4		25
	629	7.8		30
300TV-SP	225	6.9	350	15
	410	6.5		18.5
	550	6.0		22